

DEHNsense EFD | Electrical Field Detector

Your additional warning adjustable to the system!

The electric field detector (EFD) warns of the danger of electric current by detecting critical electrical voltage and alerting the user in good time before entering the danger zone. It serves as an additional measure to the 5 safety rules and significantly increases safety when working on electrical systems.

Clear advantages for safe working

Always at the right installation. If the technician accidentally approaches the wrong live switchgear cell or overhead contact line, a clear alarm is given.

Optimum response value. The response sensitivity of the EFD can be adapted to the specific installation in order to avoid false alarms.

Triple alarm. Visuall, acoustic and haptic warnings prevent penetration of the danger zone.

Smart work. The EFD can connect to the DEHNwork app, display device information, and make application-specific settings on the device.

Easy documentation. All important events of the work order are logged in the DEHNwork app.

Suitable for every work situation

Flexible!

The light and compact voltage alarm DEHNsense EFD can be worn in different ways and operated safely, even with gloves.



on the wrist

Acoustic -

frequency

through a warning

tone of changing

 \cap

Visual -

red light

visible from all

sides - flashing

0



on a helmet

0

Haptic -

the device

by vibration of

If the previously defined voltage zone is approached, a three-fold warning is given:

DEHNsense EFD works with an app

link. So that data can be conveniently

set or displayed in advance via smart-

phone or tablet (iOS or Android). In

addition, installation profiles can be

activated, newly created, or adapted to the real installation conditions via the

Triple alarm!

More comfort.

app.

Smart connection to DEHNwork app

One of a kind.

Using the DEHNwork app, you can read in a QR code generated for a specific system and transfer the individual response value to the EFD without contact.



Technical data	EFD BU 6 420 C
Part no.	740 200
Nominal voltage U_N	6 420 kV
Frequency	50 & 60 Hz
Battery capacity	750 mAh
Charging	contactless
Degree of protection	IP 65
Self-test function	yes
Handling	1-button operating concept
Operation	standby mode (continuous operation)
Internal memory	yes
Dimensions	50 x 70 x 30 mm
Transmission type	Bluetooth LE

*) Note: Required charger not included

Phone: +49 9181 906 1750 technik.support@dehn.de E-mail:



Learn more about DEHNsense EFD: de.hn/4NkvP



Subject to technical changes. The illustrations are non-binding. © Copyright 2023 DEHN SE