

## STAK 3X16 (900 588)

- Allows "V-connection" (connection of three conductors) of surge protective devices up to 16 mm<sup>2</sup>
- Allows EMC-optimised feed-through wiring according to IEC 60364-5-53





Figure without obligation



Pin-shaped terminal for EMC-optimised through-wiring of lightning current and surge arresters according to IEC 60364-5-53.

Type Part No.	STAK 3X16 900 588
Nominal voltage (a.c. / d.c.) (U <sub>N</sub> )	690 V / 1500 V
Nominal load current (a.c.) (I <sub>N</sub> )	160 A
Load current at V-wiring	80 A
Lightning impulse current (10/350 μs) (I <sub>imp</sub> )	25 kA
Rated insulation voltage (U <sub>i</sub> )	1000 V
Rated impulse withstand voltage (U <sub>imp</sub> )	8 kV
Operating temperature range (T <sub>U</sub> )	-40 °C ... +80 °C
Cross-sectional area (min.)	1.5 mm <sup>2</sup> solid / flexible
Cross-sectional area (max.)	16 mm <sup>2</sup> stranded / 10 mm <sup>2</sup> flexible
Type of connection	front
Weight	31 g
Customs tariff number (Comb. Nomenclature EU)	85369010
GTIN	4013364323933
PU	4 pc(s)

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.