



BA 30X4 STTZN R52M (810 304)



Figure without obligation

Steel strip according to EN 62561-2 with zinc coating $\geq 70 \mu\text{m}$ on average (about 500 g/m^2), for lightning protection and earth-termination systems.

| Type Part No. | BA 30X4 STTZN R52M 810 304 ✓ |
|---|--|
| Width | 30 mm |
| Thickness | 4 mm |
| Cross-section | 120 mm^2 |
| Material | St/tZn |
| Standard | EN 62561-2 |
| Zinc coating | $\geq 70 \mu\text{m}$ average (about 500 g/m^2) |
| Conductivity | $\geq 6.66 \text{ m} / \text{Ohm mm}^2$ |
| Resistivity | $\leq 0.15 \text{ Ohm mm}^2 / \text{m}$ |
| Short-circuit current (a.c. 50 Hz / d.c.) (1 s; $\leq 300 \text{ }^\circ\text{C}$) | 8.4 kA |
| Weight | 960 g/m |
| Customs tariff number (Comb. Nomenclature EU) | 72123000 |
| GTIN | 4013364019232 |
| PU | 52 m |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

Strips in different dimensions and materials are available upon request.