



## BA 40X4 STTZN R40M (810 404)




Figure without obligation

Steel strip according to EN 62561-2 with zinc coating  $\geq 70 \mu\text{m}$  on average (about  $500 \text{ g/m}^2$ ), for lightning protection and earth-termination systems.

Type Part No.	BA 40X4 STTZN R40M 810 404 ✓
Width	40 mm
Thickness	4 mm
Cross-section	$160 \text{ mm}^2$
Material	St/tZn
Standard	EN 62561-2
Zinc coating	$\geq 70 \mu\text{m}$ average (about $500 \text{ g/m}^2$ )
Conductivity	$\geq 6.66 \text{ m} / \text{Ohm mm}^2$
Resistivity	$\leq 0.15 \text{ Ohm mm}^2 / \text{m}$
Short-circuit current (a.c. 50 Hz / d.c.) (1 s; $\leq 300 \text{ }^\circ\text{C}$ )	11.2 kA
Weight	1,28 kg/m
Customs tariff number (Comb. Nomenclature EU)	72123000
GTIN	4013364048256
PU	40 m

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

Strips in different dimensions and materials are available upon request.