



## RD 8 CU F20 WEI R20M (830 108)




Figure without obligation

Copper wire according to EN 62561-2, for use in lightning protection and earth-termination systems or equipotential bonding.

| Type  | RD 8 CU F20 WEI R20M            |
|---|---------------------------------|
| Part No.                                      | 830 108 ✓                       |
| Diameter Ø conductor                          | 8 mm                            |
| Cross-section                                 | 50 mm <sup>2</sup>              |
| Material                                      | Cu                              |
| Characteristics                               | soft F20                        |
| Standard                                      | EN 62561-2                      |
| Conductivity                                  | ≥ 52.63 m / Ohm mm <sup>2</sup> |
| Resistivity                                   | ≤ 0.019 Ohm mm <sup>2</sup> / m |
| Short-circuit current (50 Hz) (1 s; ≤ 300 °C) | 9.8 kA                          |
| Weight  | 448 g/m                         |
| Customs tariff number (Comb. Nomenclature EU) | 74081100                        |
| GTIN  | 4013364080430                   |
| PU  | 20 m                            |

We reserve the right to introduce changes in performance, configuration and technology, dimensions, weights and materials in the course of technical progress. The figures are shown without obligation.

Conductor materials will be delivered in original coil weights only.

More conductor materials and components as specified in the standard series EN 62561-2 upon request.